

DECOPRIMER®

Decorative Plaster Primer

Description

Acrylic dispersion based, single component, white colored, waterborne **primer** with high adhesion strength and hiding power. Used under all cement based interior and exterior facade coating materials.

Application Areas

- Indoor and outdoor
- Horizontal and vertical applications
- For increasing adherence prior to the application of decorative plasters on thermal insulation plate plasters
- As a primer before applications on old surfaces
- Under all cement based interior and exterior facade coating materials.

Advantages

- Provides high adherence between the surface and the coating mortar
- Prevents the mortar to lose its water fast when applied prior to cement based coatings on absorbent surfaces
- Provides resistance to moisture
- Has hiding power
- Ready to use, easily and quickly applied
- Waterborne, odorless, and safe to use indoor
- Easy to apply due to its white color in thermal insulation applications.

Consumption

100 - 300 g/m² (Varies depending on the application surface.)

Packaging

15 kg plastic buckets

Technical Properties

Appearance	White colored, acrylic based dispersion
Density	~ 1.55 kg/L
Application Temperature	Between +5°C and +35°C
Drying Time	~ 6 hours
Service Temperature	-30°C / +80°C

* Application instructions and technical data provided for the products are obtained in line with our experience and the tests are implemented according to international standards, under ambient temperatures of 23±2°C and ambient relative humidity conditions of 50%±5. Higher temperatures decrease while lower temperatures increase these durations.